

Prúdový chránič , 4P



[Hz] 50	°C -25÷40	IP 20	4P	4	TH 35	Ui [V] 400
max 25	CE	EAC	VDE	UK CA		

KRD10-4/25/30-F

	[V]	In [A]	Ian [mA]	Typ prúdového chrániča	
KRD10-4/25/30-F	45776	400 AC	25	30	F 4
KRD10-4/32/30-F	45777	400 AC	32	30	F 4
KRD10-4/40/30-F	45778	400 AC	40	30	F 4
KRD10-4/63/30-F	45779	400 AC	63	30	F 4
KRD10-4/32/100-F	45780	400 AC	32	100	F 4
KRD10-4/63/100-F	45781	400 AC	63	100	F 4
KRD10-4/40/300-F	45782	400 AC	40	300	F 4
KRD10-4/63/300-F	45783	400 AC	63	300	F 4

Prúdový chránič typu F je modernejšia verzia, navrhnutá pre inštalácie s elektronikou a jednofázovými meničmi. Typ F reaguje na viac druhov reziduálneho prúdu ako klasický typ AC alebo A:

AC – striedavý sínusový prúd
A – AC + pulzujúca DC
F – všetko vyššie uvedené + prúdy so zmiešanými frekvenciami (do cca 1 kHz) a krátkodobé DC zložky do 10 mA.

Prúdový chránič , 4P



KRD10-4/25/30-F



KRD10-4/32/30-F



KRD10-4/40/30-F



KRD10-4/63/30-F



KRD10-4/32/100-F




KRD10-4/63/100-F




KRD10-4/40/300-F




KRD10-4/63/300-F




KRD10-4/25/30-F



KRD10-4/32/30-F




KRD10-4/40/30-F




KRD10-4/63/30-F


Prúdový chránič , 4P




KRD10-4/32/100-F



KRD10-4/63/100-F



KRD10-4/40/300-F



KRD10-4/63/300-F