



Kanlux



Kanlux ERGA



[V] 220-240 AC	[Hz] 50	≥ 100000	[h] 50000	ellipse $\leq 6x$ MacAdam	Ra 80	SMD
		IP 20		[°C] 5÷25		
[mm²] 0,5-2,5	[mm] Ø65-160	m 0,5m	CE	EAC	UK CA	



ERGA PIR 17W CCT-B

		[W]	[lm]	Tc [K]	[°]	SENSOR
ERGA PIR 17W CCT-B	24605	17	max 1600	3000/4000/6500	120	чорний PIR
ERGA PIR 17W CCT-W	24606	17	max 1800	3000/4000/6500	120	білий PIR
ERGA 17W CCT-B	24607	17	max 1600	3000/4000/6500	120	чорний
ERGA 17W CCT-W	24608	17	max 1800	3000/4000/6500	120	білий



ERGA PIR 17W CCT-B




ERGA PIR 17W CCT-W




ERGA 17W CCT-B



ERGA 17W CCT-W



ERGA PIR 17W CCT



ERGA 17W CCT

Date of issue: 05.02.2026, 12:45

Ми залишаємо за собою право на внесення технічних змін. Дані, що містяться в цьому матеріалі, не мають юридично обов'язкової сили.

Фотометрія: результати, отримані при тестуванні конкретного екземпляра.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

