


Kanlux



Kanlux MERA CCT




[V] 220-240 AC	[Hz] 50	[°] 120	≥15000	[h] 30000	ellipse ≤ 6x MacAdam	Ra 80
SMD			IP 20			
	0,3m	[m] 1,5	[°C] 5÷25			




MERA LED 4W CCT




		[W]	[lm]	Tc [K]	
MERA LED 4W CCT	29215	4	490 (WW) / 540 (NW) / 520 (CW)	3000/4000/6500	білий
MERA LED 8W CCT	29216	8	1000 (WW) / 1030 (NW) / 940 (CW)	3000/4000/6500	білий
MERA LED 11W CCT	29217	11	1350 (WW) / 1470 (NW) / 1430 (CW)	3000/4000/6500	білий
MERA LED 15W CCT	29218	15	1800 (WW) / 1980 (NW) / 1920 (CW)	3000/4000/6500	білий




MERA LED 4W CCT




MERA LED 8W CCT




MERA LED 11W CCT




MERA LED 15W CCT




MERA LED 4W CCT



MERA LED 8W CCT



MERA LED 11W CCT



MERA LED 15W CCT

Аксессуары

29219

MERA CCT PP

Luminaire connecting cable MERA LED CCT



Date of issue: 02.02.2026, 14:40

Ми залишаємо за собою право на внесення технічних змін. Дані, що містяться в цьому матеріалі, не мають юридично обов'язкової сили.

Фотометрія: результати, отримані при тестуванні конкретного екземпляра.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

