

# Kanlux



## Kanlux MAH PRO EM

|                |          |              |           |                             |              |         |
|----------------|----------|--------------|-----------|-----------------------------|--------------|---------|
| <br>220-240 AC | <br>50   | <br>≥80000   | <br>50000 | <br>ellipse<br>≤ 6x MacAdam | <br>80       | <br>SMD |
|                |          | <br>IP<br>66 |           | <br>0÷40                    | <br>IK<br>08 |         |
| <br>1÷2,5      | <br>0,5m |              |           |                             |              |         |



MAH PRO EM 38W 12R-NW




|                       |              |                       |                           |      |     |       |
|-----------------------|--------------|-----------------------|---------------------------|------|-----|-------|
| MAH PRO EM 38W 12R-NW | <b>38147</b> | 38 / 34,5 / 27,5 / 22 | 6100 / 5600 / 4550 / 3750 | 4000 | 110 | сірий |
| MAH PRO EM 52W 15R-NW | <b>38148</b> | 52 / 44,5 / 37 / 29,5 | 8400 / 7300 / 6200 / 5000 | 4000 | 110 | сірий |




MAH PRO EM 38W 12R-  
NW



MAH PRO EM 52W 15R-  
NW



MAH PRO EM 38W 12R-  
NW



MAH PRO EM 52W 15R-  
NW

Date of issue: 25.11.2025, 09:45

Ми залишаємо за собою право на внесення технічних змін. Дані, що містяться в цьому матеріалі, не мають юридично обов'язкової сили.

Фотометрія: результати, отримані при тестуванні конкретного екземпляра.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland [kanlux@kanlux.com](mailto:kanlux@kanlux.com)

