

## **39541** TALU IP44 DSO-B

Ring for spotlight fittings 5905339395412





















Kanlux TALU is a durable and aesthetic spotlight with an IP44/20 protection rating, designed for rooms with high humidity. Available in round or square versions, in white or matte black, with clear glass and a seal for increased tightness. Compatible with replaceable LED light sources, it's ideal for bathrooms, kitchens, and other demanding interiors.

#### **GENERAL DATA:**

Colour: black

Necessity of using self-shielding lamps: yes Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Decorative ring without a ceramic frame: yes

Replaceable light source: yes

The product is not suitable to be covered with a heat-insulating

material: yes Height [mm]: 30 Diameter [mm]: 84

Assembly hole [mm]: Ø60

### **TECHNICAL DATA:**

Rated voltage [V]: 12 AC; 12 DC; 220-240 AC

Maximum power [W]: max 10

Class of protection against electric shock: ||/|||

Enclosure material: aluminum alloy

Light source: MR16/PAR16 Light source included: no Cap (Light source): Gx5,3/GU10

Ambient temperature range to which the product can be

exposed: 5÷25

Lighting-fixture angle regulation: none

IP class: 44/20


#### LOGISTIC DATA:

Unit of measurement: unit Packaging method: 50

Number of units in the secondary packaging: 1

Number of units in the packaging: 50

Date of issue: 21.11.2025, 13:00








# **39541** TALU IP44 DSO-B

## Ring for spotlight fittings





Net unit weight [g]: 80 Grammage [g]: 118

Gross unit weight [g]: 110 Length of a unit pack [cm]: 11 Width of a unit pack [cm]: 9 Height of a unit pack [cm]: 4

Weight of a cardboard box [kg]: 5.9
Width of a cardboard box [cm]: 24
Height of a cardboard box [cm]: 22.5
Length of a cardboard box [cm]: 47.5
Volume of a cardboard box [m³]: 0.02565

