


LED garden lighting fixture

5905339181312













Kanlux GRIBLO LED is equipped with SMD LEDs characterised by high energy efficiency and durability estimated at 30,000 hrs. Kanlux GRIBLO LED is a ground recessed luminaire with a high level of tightness (IP65).

GENERAL DATA:

Colour: grey Place of assembly: In the ground Place of application: Indoors and outdoors Minimum distance from the illuminated object: 0,1m Compatible with a dimmer: no Length [mm]: 65 Width [mm]: 62 Height [mm]: 263 Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Power factor: 0.97 Maximum power [W]: 4 Class of protection against electric shock: | Diode type: LED SMD Luminous flux [lm]: 170 Colour temperature: white Correlated colour temperature [K]: 5000 **Colour consistency in McAdam ellipses**: ≤6 Colour rendering index: 80 Service life [h]: 30000 Number of on/off cycles: ≥15000 Lighting angle [°]: 35 Luminous efficiency of the lamp [lm/W]: 43 Ambient temperature range to which the product can be exposed: -15÷35 Enclosure material: aluminum alloy Protective glass material: glass Connection type: Free cable ends Wire type: H05RN-F Wire length [m]: 1 Wire diameter [mm²]: 1 Lamp-heating time [s]: <1 Lamp-ignition time [s]: <0,5 The fixture is movable vertically [°]: 180 **IP class**: 65



Kanlux 18131 GRIBLO LED SMD-NW

LED garden lighting fixture



LOGISTIC DATA:

Packaging method: 16 Number of units in the secondary packaging: 1 Number of units in the packaging: 16 Net unit weight [g]: 338 Grammage [g]: 431.25 Length of a unit pack [cm]: 8 Width of a unit pack [cm]: 8 Height of a unit pack [cm]: 27 Weight of a cardboard box [kg]: 6.9 Width of a cardboard box [kg]: 6.9 Width of a cardboard box [cm]: 32.5 Height of a cardboard box [cm]: 29 Length of a cardboard box [cm]: 32.5 Volume of a cardboard box [m³]: 0.030631

