

BL ballast

5905339185907



GENERAL DATA:

Place of application: Indoors

Compatible with a dimmer: no

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

λ : 0,98

Rated power [W]: 2 x 36

Class of protection against electric shock: I

Material: steel

Light source: T8

Ambient temperature range to which the product can be exposed: -25÷50

Connection type: Terminal block

Range of sections of wires used [mm²]: 0,5-1,5

Stabiliser type: EVG

Thermal protection: 110°C

EEL class: A2

Maximum temperature Ta [°C]: 50

IP class: 20

Tc [°C]: 70

LOGISTIC DATA:

Packaging method: 50

Number of units in the secondary packaging: 1

Number of units in the packaging: 50

Net unit weight [g]: 240

Grammage [g]: 247.4

Length of a unit pack [cm]: 32

Width of a unit pack [cm]: 3

Height of a unit pack [cm]: 3

Weight of a cardboard box [kg]: 12.37

Width of a cardboard box [cm]: 30.5

Height of a cardboard box [cm]: 18

Length of a cardboard box [cm]: 33

Volume of a cardboard box [m³]: 0.018117

ADDITIONAL INFORMATION:

- BL-3-4x14H-EVG is used for T5 fluorescent lamps current stabilisation, other models are used for T8 fluorescent lamps current stabilisation