



18730 AS 1-7M

TH35 rail-mounted automatic staircase lighting controller

5905339187307



Staircase lighting timer is used to keep lighting on for a set period of time; adjustable time range from 1min to 7min, the accuracy of the programmed time setting is 0.5min.

GENERAL DATA:

Colour: white

Place of assembly: rail TH35

Place of application: Indoors

Norm: EN60730-1; PN-EN 62052-11

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated current [A]: 16

Rated frequency [Hz]: 50

IP class: 20

LOGISTIC DATA:

Packaging method: 200

Number of units in the secondary packaging: 1

Number of units in the packaging: 200

Net unit weight [g]: 74

Grammage [g]: 91.95

Length of a unit pack [cm]: 10

Width of a unit pack [cm]: 2

Height of a unit pack [cm]: 7

Weight of a cardboard box [kg]: 18.39

Width of a cardboard box [cm]: 26.5

Height of a cardboard box [cm]: 35

Length of a cardboard box [cm]: 52

Volume of a cardboard box [m³]: 0.04823

18730 AS 1-7M

TH35 rail-mounted automatic staircase lighting controller

Żarówki/żarówki halogenowe	2300W
Świetlówki kompaktowe (CFL)	150W
Lampy LED o mocy <2W	30W
Lampy LED o mocy 2-8W	300W
Lampy LED o mocy >8W	300W
Lampy fluorescencyjne ze statecznikiem elektronicznym	600W
Lampy fluorescencyjne ze statecznikiem magnetycznym	2300 VA