

LED dustproof lighting fitting

5905339226051



Kanlux MAH LED N are hermetic luminaires designed for more demanding users. They are characterised by unique luminous efficacy reaching 105 lm/W and the possibility of connecting them in lines of even 15 luminaires (depending on the model), which allows for lighting of large spaces.

GENERAL DATA:

Colour: grey
Place of assembly: ceiling mounted
Place of application: Indoors and outdoors
Minimum distance from the illuminated object: 0,5m
Possibility of fixture-loop-through connection: yes
Compatible with a dimmer: no
Length [mm]: 1480
Width [mm]: 80
Height [mm]: 70
Number of chokes: 2
Integrated LED light source: yes


TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 50
Class of protection against electric shock: II
Lampshade material: PC
Diode type: LED SMD
Luminous flux [lm]: 5250
Colour temperature: white
Correlated colour temperature [K]: 4000
Colour consistency in McAdam ellipses: ≤ 6
Colour rendering index: 80
Service life [h]: 30000
Luminous-flux-retention factor at the end of rated service life: L70B50
Number of on/off cycles: ≥ 15000
Lighting angle [°]: X135/Y100
Luminous efficiency of the lamp [lm/W]: 105
Ambient temperature range to which the product can be exposed: $-20 \div 40$
Enclosure material: PC
Connection type: Bolt terminal block
Range of sections of wires used [mm²]: 1,5 \div 2,5
Lamp-heating time [s]: ≤ 1
Lamp-ignition time [s]: $\leq 0,5$
IK class: 08



22605 MAH-LED N 50W-NW/PC

LED dustproof lighting fitting



IP class: 65

LOGISTIC DATA:

Packaging method: 9

Number of units in the secondary packaging: 1

Number of units in the packaging: 9

Number of units per layer on a pallet: 27

Net unit weight [g]: 1720

Grammage [g]: 2022.22

Length of a unit pack [cm]: 152

Width of a unit pack [cm]: 8.5

Height of a unit pack [cm]: 7.5


Weight of a cardboard box [kg]: 18.19998

Width of a cardboard box [cm]: 27

Height of a cardboard box [cm]: 24

Length of a cardboard box [cm]: 162

Volume of a cardboard box [m³]: 0.104976



KANLUX S.A. (kat 22605) MAH-LED N 50W-NW / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 22605) MAH-LED N 50W-NW
Lampy: 1 x MAH-LED N 50W-NW

