


22800 MAH PLUS-236/4LED/PC

Dust-proof LED tube light fitting 5905339228000

















Kanlux MAH PLUS 4LED are LED equivalents of popular luminaires. Their core asset consists in the fact that they can use T8 LED light sources that are 1200 mm or 1500 mm long. This solution is perfect for industrial use.

GENERAL DATA:

Colour: grey

Place of assembly: ceiling mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m Possibility of fixture-loop-through connection: yes Power supply of T8 LED fluorescent lamps: Unilateral

Length [mm]: 1265 Width [mm]: 125 Height [mm]: 92 Number of clasps: 8

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50

Maximum power [W]: 2 x max 36

Class of protection against electric shock: I

Lampshade material: PC Light source: T8 LED Light source included: no

Cap: G13

Ambient temperature range to which the product can be

exposed: 5÷25

Enclosure material: plastic Handle material: Metal Clasp material: plastic

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 1÷2,5

IP class: 65

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 6

Number of units in the secondary packaging: 1

Number of units in the packaging: 6

Net unit weight [g]: 1600 Grammage [g]: 1950

Length of a unit pack [cm]: 127.5

Date of issue: 01.03.2024, 10:36

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





22800 MAH PLUS-236/4LED/PC

Dust-proof LED tube light fitting



Width of a unit pack [cm]: 14 Height of a unit pack [cm]: 6.5


Weight of a cardboard box [kg]: 11.7
Width of a cardboard box [cm]: 28.5
Height of a cardboard box [cm]: 22
Length of a cardboard box [cm]: 128
Volume of a cardboard box [m³]: 0.080256

ADDITIONAL INFORMATION:

 MAH PLUS 4 LEDs/PC light fixtures are designed for T8 LED 220-240 V~; 50/60 Hz light sources with one-sided power supply


KANLUX S.A. (kat 22800) MAH PLUS-236/4LED/ + GLASSv4 / LDC (Polar)


Luminaire: KANLUX S.A. (kat 22800) MAH PLUS-236/4LED/ + GLASSv4 Lamps: 2 x T8 LED GLASSv4 18W-NW



KANLUX S.A. (kat 22800) MAH PLUS-236/4LED/ + GLASSv3 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 22800) MAH PLUS-236/4LED/ + GLASSv3 Lamps: 2 x T8 LED GLASSv3 18W-NW






We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.






22800 MAH PLUS-236/4LED/PC

Dust-proof LED tube light fitting



Oprawa: KANLUX S.A. (kat 22800) MAH PLUS-236/4LED/ i GLASSv2 Lampy: 2 x T8 LED GLASSv2 18W-NW



KANLUX S.A. (kat 22800) MAH PLUS-236/4LED/ i T8 Miledo / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 22800) MAH PLUS-236/4LED/ i T8 Miledo Lampy: 2 x T8 LED 16W-NW

