


## **23145** KMB6-C10/1

Overcurrent circuit breaker, 1P

5905339231451















Circuit breaker with overcurrent protection is used to protect cables against overloads and short circuits in installations and devices.

### **GENERAL DATA:**

Colour: white

Place of assembly: rail TH35

Norm: PN-EN 60898-1 Length [mm]: 76 Width [mm]: 17.5 Height [mm]: 82

#### TECHNICAL DATA:

Rated voltage [V]: 230/400 AC

Rated current [A]: 10 Rated frequency [Hz]: 50

Ambient temperature range to which the product can be

exposed: 5÷40

Range of sections of wires used [mm<sup>2</sup>]: 1÷25

Release characteristics: C Energy-limit class: 3 Number of modules: 1

Rated short-circuit current [A]: 6000

IP class: 20

Number of poles: 1

#### LOGISTIC DATA:

Packaging method: 12


Number of units in the secondary packaging: 12

Number of units in the packaging: 120

Net unit weight [g]: 94 Grammage [g]: 104

Length of a unit pack [cm]: 2 Width of a unit pack [cm]: 7.5 Height of a unit pack [cm]: 8.5

Weight of a cardboard box [kg]: 12.48
Width of a cardboard box [cm]: 25
Height of a cardboard box [cm]: 19.5
Length of a cardboard box [cm]: 45
Volume of a cardboard box [m³]: 0.021938



We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





# **23145** KMB6-C10/1

Overcurrent circuit breaker, 1P

