


23171 KMB6-B6/3

Overcurrent circuit breaker, 3P

5905339231710



Circuit breaker with overcurrent protection is used to protect cables against overloads and short circuits in installations and devices.

GENERAL DATA:

Colour: white

Place of assembly: rail TH35

Norm: PN-EN 60898-1

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC

Rated current [A]: 6

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: 5÷40

Range of sections of wires used [mm²]: 1÷25

Release characteristics: B

Energy-limit class: 3

Number of modules: 3

Rated short-circuit current [A]: 6000

IP class: 20

Number of poles: 3

LOGISTIC DATA:

Packaging method: 4

Number of units in the secondary packaging: 4

Number of units in the packaging: 40

Net unit weight [g]: 300

Grammage [g]: 330

Length of a unit pack [cm]: 5.5

Width of a unit pack [cm]: 7.5

Height of a unit pack [cm]: 8.5

Weight of a cardboard box [kg]: 13.2

Width of a cardboard box [cm]: 25

Height of a cardboard box [cm]: 19.5

Length of a cardboard box [cm]: 45

Volume of a cardboard box [m³]: 0.021938

23171 KMB6-B6/3

Overcurrent circuit breaker, 3P