


23173 KMB6-C40/1

Overcurrent circuit breaker, 1P

5905339231734



Circuit breaker with overcurrent protection is used to protect cables against overloads and short circuits in installations and devices.

GENERAL DATA:

Colour: white
Place of assembly: rail TH35
Norm: PN-EN 60898-1
Length [mm]: 76
Width [mm]: 17.5
Height [mm]: 82

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC
Rated current [A]: 40
Rated frequency [Hz]: 50
Ambient temperature range to which the product can be exposed: 5÷40
Range of sections of wires used [mm²]: 1÷25
Release characteristics: C
Energy-limit class: 3
Number of modules: 1
Rated short-circuit current [A]: 6000
IP class: 20
Number of poles: 1

LOGISTIC DATA:

Packaging method: 12
Number of units in the secondary packaging: 12
Number of units in the packaging: 120
Net unit weight [g]: 94
Grammage [g]: 104
Length of a unit pack [cm]: 2
Width of a unit pack [cm]: 7.5
Height of a unit pack [cm]: 8.5
Weight of a cardboard box [kg]: 12.48
Width of a cardboard box [cm]: 25
Height of a cardboard box [cm]: 19.5
Length of a cardboard box [cm]: 45
Volume of a cardboard box [m³]: 0.021938

23173 KMB6-C40/1

Overcurrent circuit breaker, 1P