


## 23178 KMB6-C16/2

Miniature circuit breaker, 2P

5905339231789



Circuit breaker with overcurrent protection is used to protect cables against overloads and short circuits in installations and devices.

### GENERAL DATA:

**Place of assembly:** rail TH35

**Norm:** PN-EN 60898-1

### TECHNICAL DATA:

**Rated voltage [V]:** 230 AC

**Rated current [A]:** 16

**Rated frequency [Hz]:** 50

**Ambient temperature range to which the product can be exposed:** 5÷40

**Range of sections of wires used [mm<sup>2</sup>]:** 1÷25

**Release characteristics:** C

**Energy-limit class:** 3

**Number of modules:** 2

**Rated short-circuit current [A]:** 6000

**IP class:** 20

**Number of poles:** 2

### LOGISTIC DATA:

**Packaging method:** 6

**Number of units in the secondary packaging:** 6

**Number of units in the packaging:** 60

**Net unit weight [g]:** 188

**Grammage [g]:** 203.33

**Length of a unit pack [cm]:** 4

**Width of a unit pack [cm]:** 7.5

**Height of a unit pack [cm]:** 8.5

**Weight of a cardboard box [kg]:** 12.1998

**Width of a cardboard box [cm]:** 25

**Height of a cardboard box [cm]:** 19.5

**Length of a cardboard box [cm]:** 45

**Volume of a cardboard box [m<sup>3</sup>]:** 0.021938