


## 23185 KRD6-4/63/30

Residual-current circuit breaker, 4P

5905339231857



Residual current circuit breaker: is used for additional protection against electric shock, designed for work in sinusoidal alternating current circuits (AC type) and sinusoidal alternating and pulsating current with DC component (A type).

### GENERAL DATA:

**Colour:** white

**Place of assembly:** rail TH35

**Norm:** PN-EN 61008-1

### TECHNICAL DATA:

**Rated voltage [V]:** 400 AC

**Rated current [A]:** 63

**Rated frequency [Hz]:** 50

**Ambient temperature range to which the product can be exposed:** -25÷40

**Range of sections of wires used [mm<sup>2</sup>]:** do 35

**Residual-current protection type:** AC

**Number of modules:** 4

**Differential-rated current [mA]:** 30

**IP class:** 20

**Number of poles:** 4

### LOGISTIC DATA:

**Packaging method:** 30

**Number of units in the secondary packaging:** 1

**Number of units in the packaging:** 30

**Net unit weight [g]:** 340

**Grammage [g]:** 388.67

**Length of a unit pack [cm]:** 9

**Width of a unit pack [cm]:** 8

**Height of a unit pack [cm]:** 8

**Weight of a cardboard box [kg]:** 11.6601

**Width of a cardboard box [cm]:** 28

**Height of a cardboard box [cm]:** 18.5

**Length of a cardboard box [cm]:** 47

**Volume of a cardboard box [m<sup>3</sup>]:** 0.024346

## **23185** KRD6-4/63/30

---

Residual-current circuit breaker, 4P