

23193 KRD6-4/63/30-A

Residual-current circuit breaker, 4P

5905339231932



Residual current circuit breaker: is used for additional protection against electric shock, designed for work in sinusoidal alternating current circuits (AC type) and sinusoidal alternating and pulsating current with DC component (A type).

GENERAL DATA:

Colour: white
Place of assembly: rail TH35
Norm: PN-EN 61008-1

TECHNICAL DATA:

Rated voltage [V]: 400 AC
Rated current [A]: 63
Rated frequency [Hz]: 50
Ambient temperature range to which the product can be exposed: -25÷40
Range of sections of wires used [mm²]: do 35
Residual-current protection type: A
Number of modules: 4
Differential-rated current [mA]: 30
IP class: 20
Number of poles: 4

LOGISTIC DATA:

Packaging method: 30
Number of units in the secondary packaging: 1
Number of units in the packaging: 30
Net unit weight [g]: 340
Grammage [g]: 390.67
Length of a unit pack [cm]: 9
Width of a unit pack [cm]: 8
Height of a unit pack [cm]: 8
Weight of a cardboard box [kg]: 11.7201
Width of a cardboard box [cm]: 28
Height of a cardboard box [cm]: 18.5
Length of a cardboard box [cm]: 47
Volume of a cardboard box [m³]: 0.024346

23193 KRD6-4/63/30-A

Residual-current circuit breaker, 4P