


23195 KRD6-2/25/300

Residual-current circuit breaker, 2P

5905339231956



Residual current circuit breaker: is used for additional protection against electric shock, designed for work in sinusoidal alternating current circuits (AC type) and sinusoidal alternating and pulsating current with DC component (A type).

GENERAL DATA:

Colour: white

Place of assembly: rail TH35

Norm: PN-EN 61008-1

TECHNICAL DATA:

Rated voltage [V]: 230 AC

Rated current [A]: 25

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -25÷40

Residual-current protection type: AC

Number of modules: 2

Differential-rated current [mA]: 300

IP class: 20

Number of poles: 2

LOGISTIC DATA:

Packaging method: 60

Number of units in the secondary packaging: 1

Number of units in the packaging: 60

Net unit weight [g]: 210

Grammage [g]: 242.33

Length of a unit pack [cm]: 9

Width of a unit pack [cm]: 4

Height of a unit pack [cm]: 8.5

Weight of a cardboard box [kg]: 14.5398

Width of a cardboard box [cm]: 28

Height of a cardboard box [cm]: 18.5

Length of a cardboard box [cm]: 47

Volume of a cardboard box [m³]: 0.024346