


23197 KRD6-4/100/30

Residual-current circuit breaker, 4P 5905339231970







Residual current circuit breaker: is used for additional protection against electric shock, designed for work in sinusoidal alternating current circuits (AC type) and sinusoidal alternating and pulsating current with DC component (A type).

GENERAL DATA:

Colour: white

Place of assembly: rail TH35

Norm: PN-EN 61008-1

TECHNICAL DATA:

Rated voltage [V]: 400 AC Rated current [A]: 100 Rated frequency [Hz]: 50

Ambient temperature range to which the product can be

exposed: -25÷40

Range of sections of wires used [mm²]: do 35

Residual-current protection type: AC

Number of modules: 4

Differential-rated current [mA]: 30

IP class: 20

Number of poles: 4

LOGISTIC DATA:

Packaging method: 30

Number of units in the secondary packaging: 1

Number of units in the packaging: 30

Net unit weight [g]: 340 Grammage [g]: 390.67

Length of a unit pack [cm]: 9 Width of a unit pack [cm]: 8 Height of a unit pack [cm]: 8

Weight of a cardboard box [kg]: 11.7201 Width of a cardboard box [cm]: 28 Height of a cardboard box [cm]: 18.5 Length of a cardboard box [cm]: 47 Volume of a cardboard box [m³]: 0.024346

Date of issue: 15.11.2022, 12:29

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





23197 KRD6-4/100/30

Residual-current circuit breaker, 4P

