


23253 KMC-40-20

Modular contactor, 230 VAC control voltage

5905339232533



Contactor is used for automatic activation of electricity receivers. Categories of use AC7a, AC7b.

GENERAL DATA:

Utilisation category: AC-7A, AC-7B

Colour: white

Place of assembly: rail TH35

Place of application: Indoors

Norm: PN-EN 60947-4-1

TECHNICAL DATA:

Rated voltage [V]: 230 AC

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -25÷40

Connection type: Terminal block

Number of n.o./n.c. contacts: 2/0

Number of modules: 2

Rated power AC-7A/230: 8,5kW

Rated power AC-7B/230: 2,5kW

Coil-supply voltage [V]: 230V AC 50/60Hz

Rated current I(N) AC-7A/AC-1: 40A

Rated current I(N) AC-7B/AC-1: 15A

IP class: 20

LOGISTIC DATA:

Packaging method: 6

Number of units in the secondary packaging: 6

Number of units in the packaging: 60

Net unit weight [g]: 228

Grammage [g]: 245

Length of a unit pack [cm]: 3.5

Width of a unit pack [cm]: 7

Height of a unit pack [cm]: 8.5

Weight of a cardboard box [kg]: 14.7

Width of a cardboard box [cm]: 24.5

Height of a cardboard box [cm]: 20

Length of a cardboard box [cm]: 46

Volume of a cardboard box [m³]: 0.02254

23253 KMC-40-20

Modular contactor, 230 VAC control voltage