


23623 KDB-F24P

KDB-series distribution board

5905339236234



KDB series switchboards meeting the requirement for heat resistance at the temperature of 650°C, can be used on non-flammable surfaces only (e.g. full solid walls made of non-combustible materials). They cannot be used on flammable surfaces (e.g. plasterboard, wood boards, etc.), on the so-called "hollow walls" or on technical sections

GENERAL DATA:

Colour: white
Door colour: white
Place of assembly: Recessed mount in the wall
Norm: PN-EN 62208
Length [mm]: 317
Width [mm]: 109
Height [mm]: 310

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC
Rated current [A]: 63
Rated frequency [Hz]: 50
Class of protection against electric shock: II
Material: plastic
Number of modules: 2x12P
Temperature resistance [°C]: 650
IK class: 07
IP class: 30
number of rows: 2

LOGISTIC DATA:

Packaging method: 5
Number of units in the packaging: 5
Net unit weight [g]: 1314
Grammage [g]: 1804
Length of a unit pack [cm]: 33
Width of a unit pack [cm]: 11.5
Height of a unit pack [cm]: 32
Weight of a cardboard box [kg]: 9.02
Width of a cardboard box [cm]: 35
Height of a cardboard box [cm]: 34
Length of a cardboard box [cm]: 59.5
Volume of a cardboard box [m³]: 0.070805

23623 KDB-F24P

KDB-series distribution board