

23860 DRIVE LED 0-15W 12VDC


CV power supply unit

5905339238603



















Kanlux DRIVE is an electronic constant-voltage power supply unit with power of 15 W. It is used for powering LED belts such as LEDS P or LEDS B.

GENERAL DATA:

Colour: anthracite

Place of application: Indoors

Possibility of installation on a normally flammable

surface: yes Length [mm]: 112 Width [mm]: 45 Height [mm]: 29

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 0-15

Class of protection against electric shock: ||

Material: plastic

Ambient temperature range to which the product can be

exposed: 5÷25

Connection type: Terminal block

Range of sections of wires used [mm 2]: 0,75 \div 1,5

Supply-cord type: constant-voltage

Thermal protection: 110°C
Short-circuit protection: yes
Maximum temperature Ta [°C]: 35
Input voltage - PRI [V]: 220-240
Output voltage - SEC [V]: 12 DC
Output current - sec [ma]: max 1250

IP class: 20 **Tc [°C]**: 75

LOGISTIC DATA:

Packaging method: 100

Number of units in the secondary packaging: 1

Number of units in the packaging: 100 Number of units per layer on a pallet: 400

Net unit weight [g]: 82 Grammage [g]: 117

Length of a unit pack [cm]: 6 Width of a unit pack [cm]: 5 Height of a unit pack [cm]: 13

Weight of a cardboard box [kg]: 11.7 Width of a cardboard box [cm]: 32

Date of issue: 15.11.2022, 10:20

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





23860 DRIVE LED 0-15W 12VDC

CV power supply unit

Height of a cardboard box [cm]: 22 Length of a cardboard box [cm] : 67

Volume of a cardboard box [m³]: 0.047168

Date of issue: 15.11.2022, 10:20

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

