


23954 NILAN 19-C

Ring for spotlight fittings 5905339239549









Colour: chrome Necessity of using self-shielding lamps : yes Place of assembly: Recessed mount in the ceiling Place of application : Indoors Minimum distance from the illuminated object : 0,5m Decorative ring without a ceramic frame : yes The product is not suitable to be covered with a heat-insulating material: yes Height [mm]: 25 Diameter [mm]: 77 Assembly hole [mm]: Ø60-70

TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC; 220-240 AC Maximum power [W]: max 10 Class of protection against electric shock : II/III Light source : MR11/PAR11 Light source included : no Cap: Gx5,3/GU10 Ambient temperature range to which the product can be exposed: 5÷25 Enclosure material: steel Lighting-fixture angle regulation : in one axis Lighting-fixture angle regulation [°] : 15 IP class: 20

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 50 Number of units in the secondary packaging: 1 Number of units in the packaging: 50 Net unit weight [g]: 54 Grammage [g]: 79.6 Length of a unit pack [cm]: 8.5 Width of a unit pack [cm]: 3.5 Height of a unit pack [cm]: 3.5 Weight of a cardboard box [kg]: 3.98 Width of a cardboard box [cm]: 20 Height of a cardboard box [cm]: 19 Length of a cardboard box [cm]: 45 Volume of a cardboard box [m³]: 0.0171

Date of issue: 22.02.2023, 11:56 We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





23954 NILAN 19-C

Ring for spotlight fittings

ADDITIONAL INFORMATION:

Decorative ring without a ceramic frame

