



24065 KMP-1,6

KMP motor protection switch

5905339240651









Motor circuit breaker is used for protect three-phase motor circuits. We have accessories adjusted to the breakers - auxiliary contacts, triggers and tight housing.

GENERAL DATA:

Utilisation category: AC-3

Colour: white

Place of assembly: rail TH35 Norm: PN-EN 60947-4-1

TECHNICAL DATA:

Connection type: Terminal block
Rated breaking voltage Ue [V]: 400

Thermal-power Ithe [A]: 1.6

IP class: 20

Instantaneous release [A]: 22.5

Overcurrent-release setpoint range [A]: 1-1,6 3-phase rated power - 230/240V [kW]: 0.18 3-phase rated power - 400 V [kW]: 0.37 3-phase rated power - 440 V [kW]: 0.37 3-phase rated power - 500 V [kW]: 0.37 3-phase rated power - 690 V [kW]: 0.75 Rated insulation voltage UI [V]: 690

Rated impulse withstand voltage Uimp [V]: 6000

LOGISTIC DATA:

Packaging method: 50

Number of units in the secondary packaging: 1


Number of units in the packaging: 50

Net unit weight [g]: 250 Grammage [g]: 271.4

Length of a unit pack [cm]: 9 Width of a unit pack [cm]: 4.5 Height of a unit pack [cm]: 8.5

Weight of a cardboard box [kg]: 13.57 Width of a cardboard box [cm]: 25.5 Height of a cardboard box [cm]: 18 Length of a cardboard box [cm]: 47

Volume of a cardboard box [m³]: 0.021573







24065 KMP-1,6

KMP motor protection switch

