



24072 KMP-23,0

KMP motor protection switch

5905339240729









Motor circuit breaker is used for protect three-phase motor circuits. We have accessories adjusted to the breakers - auxiliary contacts, triggers and tight housing.

GENERAL DATA:

Utilisation category: AC-3

Colour: white

Place of assembly: rail TH35 Norm: PN-EN 60947-4-1

TECHNICAL DATA:

Connection type: Terminal block
Rated breaking voltage Ue [V]: 400

Thermal-power Ithe [A]: 23

IP class: 20

Instantaneous release [A]: 327

Overcurrent-release setpoint range [A]: 17-23
3-phase rated power - 230/240V [kW]: 5.5
3-phase rated power - 400 V [kW]: 9
3-phase rated power - 440 V [kW]: 11
3-phase rated power - 500 V [kW]: 11
3-phase rated power - 690 V [kW]: 18.5

Rated insulation voltage UI [V]: 690

Rated impulse withstand voltage Uimp [V]: 6000

LOGISTIC DATA:

Packaging method: 50

Number of units in the secondary packaging: 1

Number of units in the packaging: 50

Net unit weight [g]: 260 Grammage [g]: 281.4

Length of a unit pack [cm]: 9 Width of a unit pack [cm]: 4.5 Height of a unit pack [cm]: 8.5

Weight of a cardboard box [kg]: 14.07 Width of a cardboard box [cm]: 25.5 Height of a cardboard box [cm]: 18 Length of a cardboard box [cm]: 47

Volume of a cardboard box [m³]: 0.021573



We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





24072 KMP-23,0

KMP motor protection switch

