


24101 KCP-09-24

KCP power contactor

5905339241016







Power contactors are designed to connect AC circuits in AC3 utilisation category. Current range of the offer up to 32A, supply voltage 24VAC or 230VAC. As a standard, contactors have a 1NO auxiliary contact.

GENERAL DATA:

Utilisation category: AC-3 Colour: white Place of assembly: rail TH35 Norm: PN-EN 60947-4-1

TECHNICAL DATA:

Rated frequency [Hz]: 50 Connection type: Terminal block Electric connection frequency AC-3 [number/h]: 1200 Electric connection frequency AC-4 [number/h]: 300 Mechanical connection frequency [number/h]: 3600 Impedancja na biegun [mΩ]: 2.5 Rated operating power AC-3 220-240V: 2,2kW Rated operating power AC-3 380-400V: 4kW Rated operating power AC-3 415 V: 4kW Rated operating power AC-3 440 V: 4kW Rated operating power AC-3 660-690V: 5,5kW Coil-supply voltage [V]: 24 AC Rated breaking voltage Ue [V]: 400 Conventional thermal current Ith [A]: 25 Tightening force [Nm]: 1,7Nm **IP class**: 20 Main contacts: 3 Auxiliary contacts: 1 Rated insulation voltage UI [V]: 690 Rated impulse withstand voltage Uimp [V]: 6000 Rated operational current le [A]: 9 Rated operating current 380V - In AC-3: 9A Rated operating current 380V - In AC-4: 3,5A Rated operating current 440V - In AC-1: 20A Rated operating current 660V - In AC-3: 6,6A Rated operating current 660V - In AC-4: 1,5A Żywotność elektryczna (x10³) AC-3: 1000 Żywotność elektryczna (x10³) AC-4: 200 Żywotność mechaniczna (x10°): 10Nm



24101 KCP-09-24

KCP power contactor

LOGISTIC DATA:

Packaging method: 50 Number of units in the secondary packaging: 1 Number of units in the packaging: 50 Net unit weight [g]: 336 Grammage [g]: 358 Length of a unit pack [cm]: 8 Width of a unit pack [cm]: 5 Height of a unit pack [cm]: 9 Weight of a cardboard box [kg]: 17.9 Width of a cardboard box [cm]: 26 Height of a cardboard box [cm]: 21 Length of a cardboard box [cm]: 40 Volume of a cardboard box [m³]: 0.02184



