


24105 KCP-18-24

KCP power contactor

5905339241054







Power contactors are designed to connect AC circuits in AC3 utilisation category. Current range of the offer up to 32A, supply voltage 24VAC or 230VAC. As a standard, contactors have a 1NO auxiliary contact.

GENERAL DATA:

Utilisation category: AC-3

Colour: white

Place of assembly: rail TH35 Norm: PN-EN 60947-4-1

TECHNICAL DATA:

Rated frequency [Hz]: 50

Connection type: Terminal block

Electric connection frequency AC-3 [number/h]: 1200 Electric connection frequency AC-4 [number/h]: 300 Mechanical connection frequency [number/h]: 3600

Impedancja na biegun [mΩ]: 2.5

Rated operating power AC-3 220-240V: 4kW
Rated operating power AC-3 380-400V: 7,5kW
Rated operating power AC-3 415 V: 9kW
Rated operating power AC-3 440 V: 9kW
Rated operating power AC-3 660-690V: 10kW

Coil-supply voltage [V]: 24 AC Rated breaking voltage Ue [V]: 400 Conventional thermal current Ith [A]: 32

Tightening force [Nm]: 1,7Nm

IP class: 20 Main contacts: 3 Auxiliary contacts: 1


Rated insulation voltage UI [V]: 690

Rated impulse withstand voltage Uimp [V]: 6000

Rated operational current le [A]: 18

Rated operating current 380V - In AC-3: 18A
Rated operating current 380V - In AC-4: 7,7A
Rated operating current 440V - In AC-1: 32A
Rated operating current 660V - In AC-3: 12A
Rated operating current 660V - In AC-4: 3,8A
Żywotność elektryczna (x10³) AC-3: 1000
Żywotność elektryczna (x10³) AC-4: 200
Żywotność mechaniczna (x10°): 10Nm









24105 KCP-18-24

KCP power contactor

LOGISTIC DATA:

Packaging method: 50

Number of units in the secondary packaging: $\boldsymbol{1}$

Number of units in the packaging: 50

Net unit weight [g]: 348 Grammage [g]: 370

Length of a unit pack [cm]: 8 Width of a unit pack [cm]: 5 Height of a unit pack [cm]: 9

Weight of a cardboard box [kg]: 18.5 Width of a cardboard box [cm]: 26 Height of a cardboard box [cm]: 21 Length of a cardboard box [cm]: 40 Volume of a cardboard box [m³]: 0.02184

ACCESSORIES:

24110 KCP-AX11 Blok styków pomocniczych do styczników

mocy - frontowe

TO THE STATE OF TH

24111 KCP-AX22 Blok styków pomocniczych do styczników

mocy - frontowe





