


24106 KCP-25-230

KCP power contactor

5905339241061







Power contactors are designed to connect AC circuits in AC3 utilisation category. Current range of the offer up to 32A, supply voltage 24VAC or 230VAC. As a standard, contactors have a 1NO auxiliary contact.

GENERAL DATA:

Utilisation category: AC-3

Colour: white

Place of assembly: rail TH35 Norm: PN-EN 60947-4-1

TECHNICAL DATA:

Rated frequency [Hz]: 50

Connection type: Terminal block

Electric connection frequency AC-3 [number/h]: 1200 Electric connection frequency AC-4 [number/h]: 300 Mechanical connection frequency [number/h]: 3600

Impedancja na biegun $[m\Omega]$: 2

Rated operating power AC-3 220-240V: 5,5kW
Rated operating power AC-3 380-400V: 11kW
Rated operating power AC-3 415 V: 11kW
Rated operating power AC-3 440 V: 11kW
Rated operating power AC-3 660-690V: 15kW

Coil-supply voltage [V]: 230 AC Rated breaking voltage Ue [V]: 400 Conventional thermal current Ith [A]: 40

Tightening force [Nm]: 2,5Nm

IP class: 20 Main contacts: 3 Auxiliary contacts: 1


Rated insulation voltage UI [V]: 690

Rated impulse withstand voltage Uimp [V]: 6000

Rated operational current le [A]: 25

Rated operating current 380V - In AC-3: 25A
Rated operating current 380V - In AC-4: 8,5A
Rated operating current 440V - In AC-1: 40A
Rated operating current 660V - In AC-3: 18A
Rated operating current 660V - In AC-4: 4,4A
Żywotność elektryczna (x10³) AC-3: 1000
Żywotność elektryczna (x10³) AC-4: 200
Żywotność mechaniczna (x106): 10Nm









24106 KCP-25-230

KCP power contactor

LOGISTIC DATA:

Packaging method: 50

Number of units in the secondary packaging: $\boldsymbol{1}$

Number of units in the packaging: 50

Net unit weight [g]: 520 Grammage [g]: 548

Length of a unit pack [cm]: 8.5
Width of a unit pack [cm]: 6
Height of a unit pack [cm]: 10.5
Weight of a cardboard box [kg]: 27.4
Width of a cardboard box [cm]: 26
Height of a cardboard box [cm]: 21
Length of a cardboard box [cm]: 40
Volume of a cardboard box [m³]: 0.02184

ACCESSORIES:

24110 KCP-AX11 Blok styków pomocniczych do styczników

mocy - frontowe



24111 KCP-AX22 Blok styków pomocniczych do styczników

mocy - frontowe





We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

