


LED tape

5905339245120











Kanlux LEDS-B are modern strips of decorative character. Perfect for home use where they can create unique arrangements limited by our imagination only. They are characterised by high flexibility, good adhesion and high durability. Depending on the place in which we want to add more light or which we wish to highlight, we can choose the light colour suiting our preferences.

GENERAL DATA:

Place of application: Indoors Minimum distance from the illuminated object: 0,1m Length [mm]: 5000 Width [mm]: 8 Height [mm]: 5000 Depth [mm]: 1 Mercury content: no

TECHNICAL DATA:

Rated voltage [V]: 12 DC **Rated power [W]**: 1m = 4,8 Class of protection against electric shock: III Diode type: LED SMD Useful luminous flux of the light source Φ use [Im]: 0.5m=200 Useful luminous flux of the light source **Quse** [Im]: in sphere (360°) Colour temperature: cold white Correlated colour temperature [K]: 6000-7500 **Colour consistency in McAdam ellipses**: ≤6 Colour rendering index: 80 Rated lamp-service life [h]: 15000 Number of on/off cycles: ≥ 10000 Ambient temperature range to which the product can be exposed: 5÷25 Connection type: Free cable ends **IP class**: 54


LOGISTIC DATA:

Packaging method: 25 Number of units in the secondary packaging: 25 Number of units in the packaging: 50 Net unit weight [g]: 90 Grammage [g]: 184 Length of a unit pack [cm]: 20.5



Kanlux 24512 LEDS-B 4.8W/M IP54-CW

LED tape



Width of a unit pack [cm]: 1 Height of a unit pack [cm]: 22.5 Weight of a cardboard box [kg]: 9.2 Width of a cardboard box [cm]: 32.5 Height of a cardboard box [cm]: 28.5 Length of a cardboard box [cm] : 51 Volume of a cardboard box [m³]: 0.047239

