


## LED light source

5905339245243











Kanlux ZUBI LED are energy-saving sources. Their additional functional benefits include the small size and the milky lampshade reducing the glare effect. They provide smart and aesthetic look. The construction of Kanlux ZUBI sources guarantees a wide light emission angle, owing to which they are perfect for all open luminaires and chandeliers.

#### GENERAL DATA:

Colour: white Lamp designed for decorative lighting: Not applicable Compatible with a dimmer: no Width [mm]: 19.5 Height [mm]: 54 Diameter [mm]: 19.5 Depth [mm]: 19.5 Mercury content: no


#### **TECHNICAL DATA:**

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Lamp-power factor: 0.4 Rated power [W]: 4 Material: plastic Lampshade material: plastic Light source: G9 Diode type: LED SMD Total rated luminous flux [lm]: 500 Useful luminous flux of the light source **Quse** [Im]: 500 Useful luminous flux of the light source **Quse** [Im]: in sphere (360°) Colour temperature: Warm white Correlated colour temperature [K]: 3000 **Colour consistency in McAdam ellipses**: ≤6 Colour rendering index: 80 **Cap**: G9 Rated lamp-service life [h]: 15000 Number of on/off cycles: ≥15000 Rated beam angle [°]: 280 Rated light level [°]: 280 Lamp rated current [mA]: 33 Annual power consumption [kWh/1000h]: 4 Luminous efficiency of the lamp [lm/W]: 125 **Ignition time [s]**: ≤0,5 Lamp-heating time to 60% of the full luminous flux [s]: Negligible





# LED light source






Lamp-heating time to 95% [s]: <2 Lamp premature-failure indicator: <5% po 1000h Lamp service life factor after the period of 6000h [%]:  $\geq$ 90 Luminous flux retention factor at the end of rated service life [%]:  $\geq$ 70 Luminous flux retention factor after the period of 6000h [%]:  $\geq$ 80 Declaration of equality in power rating [W]: 42 Light source shape: kapsulka

### LOGISTIC DATA:

Packaging method: 10 Number of units in the secondary packaging: 10 Number of units in the packaging: 100 Net unit weight [g]: 16 Grammage [g]: 51.8 Length of a unit pack [cm]: 11.5 Width of a unit pack [cm]: 2.5 Height of a unit pack [cm]: 2.5 Height of a cardboard box [kg]: 5.18 Width of a cardboard box [kg]: 5.18 Width of a cardboard box [cm]: 34 Height of a cardboard box [cm]: 21.5 Length of a cardboard box [cm]: 63.5 Volume of a cardboard box [m<sup>3</sup>]: 0.046419






LED light source

KANLUX S.A. (kat 24524) ZUBI HI LED4WG9-WW / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 24524) ZUBI HI LED4WG9-WW Lampy: 1 x ZUBI HI LED4WG9-WW



C90 - C270