


24641 TYBIA LED 38W-NW-SE

Ceiling-mounted LED light fitting

5905339246417



Kanlux TYBIA LED is a general lighting luminaire using SMD diodes. When mounted in corridors, staircases, social or utility rooms, TYBIA LED allows for significant savings related to both reduced energy consumption and the long-term maintenance-free operation.

GENERAL DATA:

Colour: grey / white
Place of assembly: ceiling mounted
Place of application: Indoors
Micro-interval between relay contacts: yes
Minimum distance from the illuminated object: 0,5m
Compatible with a dimmer: no
Wykrywanie ruchu: yes
Length [mm]: 410
Width [mm]: 410
Height [mm]: 61
Sensitivity regulation: yes
Mercury content: no
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 38
Class of protection against electric shock: I
Lampshade material: PMMA
Diode type: LED SMD
Luminous flux of the light fitting [lm]: 3800
Useful luminous flux of the light source Φ_{use} [lm]: 5700
Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)
Colour temperature: white
Correlated colour temperature [K]: 4000
Colour consistency in McAdam ellipses: ≤ 6
Colour rendering index: 80
Service life [h]: 30000
Luminous-flux-retention factor at the end of rated service life: L70B50
Number of on/off cycles: ≥ 20000
Lighting angle [°]: 110
Luminous efficiency of the lamp [lm/W]: 100
Ambient temperature range to which the product can be exposed: 5÷25
Enclosure material: aluminum alloy

Ceiling-mounted LED light fitting



Sensor type: microwave

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 1-2,5

Sensor-operation time [second-minute]: 5-15

Lamp-heating time [s]: ≤1

Lamp-ignition time [s]: ≤0,5

Sensor-operation frequency [MHz]: 5800

sensor working angle [°]: H360

Illumination-level setpoint by which the sensor detects movement [lx]: 2/10/50/off

IP class: 20

Sensor range[m]: max 9,5

LOGISTIC DATA:

Packaging method: 6

Number of units in the secondary packaging: 1

Number of units in the packaging: 6

Net unit weight [g]: 2320

Grammage [g]: 2640

Length of a unit pack [cm]: 42

Width of a unit pack [cm]: 42

Height of a unit pack [cm]: 7.5

Weight of a cardboard box [kg]: 15.84

Width of a cardboard box [cm]: 43


Height of a cardboard box [cm]: 44

Length of a cardboard box [cm]: 48

Volume of a cardboard box [m³]: 0.090816

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website



24641 TYBIA LED 38W-NW-SE

Ceiling-mounted LED light fitting

