

24731 DOMO 01-1230-102 bi

Socket Outlet Earthed - With Protection Cover - FireProof Plastic

5905339247315



GENERAL DATA:

Colour: white
Place of assembly: Recessed mount in the wall
Width [mm]: 71
Height [mm]: 71
Diameter of an installation box: 60
Installation depth: 25
Number of sockets: 1

TECHNICAL DATA:

Rated voltage [V]: 250 AC
Rated current [A]: 16
Class of protection against electric shock: I
Material: PC
Material of contacts: CuSn94
Earthing type: type F
Terminal type: Screw terminal
Plastic: PC
IP class: 44

LOGISTIC DATA:

Packaging method: 10
Number of units in the secondary packaging: 10
Number of units in the packaging: 120
Net unit weight [g]: 82
Grammage [g]: 97.17
Length of a unit pack [cm]: 10
Width of a unit pack [cm]: 5
Height of a unit pack [cm]: 14
Weight of a cardboard box [kg]: 11.6604
Width of a cardboard box [cm]: 26.5
Height of a cardboard box [cm]: 32
Length of a cardboard box [cm]: 44
Volume of a cardboard box [m³]: 0.037312

24731 DOMO 01-1230-102 bi

Socket Outlet Earthed - With Protection Cover - FireProof Plastic

