




25128 LOGI 02-1021-103 kr

Control Switch (no symbol)

5905339251282









A NO switch is used to control time relays with an impulse (controlling the circuit of a lamp or a group of lamps, controlling door and gate mechanisms).

GENERAL DATA:

Colour: Ecru

Place of assembly: Recessed mount in the wall

Width [mm]: 71 Height [mm]: 71

Diameter of an installation box: 60

Installation depth: 25

TECHNICAL DATA:

Rated voltage [V]: 250 AC Material of contacts: CuZn70 Terminal type: Screw terminal

Plastic: ABS

Number of levers: 1 Rated current [AX]: 10

IP class: 20

LOGISTIC DATA:

Packaging method: 10

Number of units in the secondary packaging: 10

Number of units in the packaging: 120

Net unit weight [g]: 70 Grammage [g]: 82.25

Length of a unit pack [cm]: 10 Width of a unit pack [cm]: 4 Height of a unit pack [cm]: 14

Weight of a cardboard box [kg]: 9.87
Width of a cardboard box [cm]: 25.5
Height of a cardboard box [cm]: 32
Length of a cardboard box [cm]: 44
Volume of a cardboard box [m³]: 0.035904

Date of issue: 15.11.2022, 22:55

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.








25128 LOGI 02-1021-103 kr

Control Switch (no symbol)



We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

