MOW ION
by **Kanlux**

 LOGI

25151 LOGI 02-1253-103 kr

Type E double power socket with earthing terminal

5905339251510

CE | EAC | PZH | UKCA | (symbol)

A double grounded socket outlet allows you to power electrical circuits with a maximum load of 16A.

GENERAL DATA:

Colour: Ecru
Place of assembly: Recessed mount in the wall
Width [mm]: 71
Height [mm]: 71
Diameter of an installation box: 60
Installation depth: 25
Number of sockets: 2

TECHNICAL DATA:

Rated voltage [V]: 250 AC
Rated current [A]: 16
Class of protection against electric shock: I
Material of contacts: CuZn70
Earthing type: Type E
Terminal type: Screw terminal
Plastic: ABS
IP class: 20

LOGISTIC DATA:

Packaging method: 10
Number of units in the secondary packaging: 10
Number of units in the packaging: 120
Net unit weight [g]: 84
Grammage [g]: 101.67
Length of a unit pack [cm]: 10
Width of a unit pack [cm]: 5
Height of a unit pack [cm]: 14
Weight of a cardboard box [kg]: 12.2004
Width of a cardboard box [cm]: 25.5
Height of a cardboard box [cm]: 32
**Length of a cardboard box [cm]** : 44
Volume of a cardboard box [m³]: 0.035904

EN

LOGI

25151   LOGI 02-1253-103 kr

Type E double power socket with earthing terminal

EN