




25203 LOGI 02-1210-143 sr

Socket Outlet Without Earth - FireProof Plastic

5905339252036









A non-grounded single socket outlet allows you to power an electrical circuit with a maximum load of 16A.

GENERAL DATA:

Colour: silver

Place of assembly: Recessed mount in the wall

Width [mm]: 71 Height [mm]: 71

Diameter of an installation box: 60

Installation depth: 25 **Number of sockets**: 1

TECHNICAL DATA:

Rated voltage [V]: 250 AC Rated current [A]: 16

Class of protection against electric shock: ||

Material of contacts: CuZn70

Earthing type: 2P

Terminal type: Screw terminal

Plastic: ABS IP class: 20

LOGISTIC DATA:

Packaging method: 10

Number of units in the secondary packaging: 10

Number of units in the packaging: 120

Net unit weight [g]: 58 Grammage [g]: 70.25

Length of a unit pack [cm]: 10 Width of a unit pack [cm]: 4 Height of a unit pack [cm]: 14

Weight of a cardboard box [kg]: 8.43
Width of a cardboard box [cm]: 25.5
Height of a cardboard box [cm]: 32
Length of a cardboard box [cm]: 44
Volume of a cardboard box [m³]: 0.035904

Date of issue: 15.11.2022, 21:59

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.







25203 LOGI 02-1210-143 sr

Socket Outlet Without Earth - FireProof Plastic

