

25338 BIURO 04-2010-102 bi

PIR motion sensor

5905339253385



GENERAL DATA:

Colour: white
Place of assembly: slot 45x45
Place of application: Indoors
Micro-interval between relay contacts: yes
Length [mm]: 45
Width [mm]: 47
Height [mm]: 45
Sensitivity regulation: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Class of protection against electric shock: II
Material: plastic
Sensor type: PIR
Connection type: Terminal block
sensor working angle [°]: 80
Number of modules: 2
Maximum load [W]: 400
Maximum operating time [min]: 10
Minimum operating time[s]: 5
Illumination-level setpoint by which the sensor detects movement [lx]: 1-2000
IP class: 20
Sensor range[m]: 3,5-9

LOGISTIC DATA:

Packaging method: 36
Number of units in the secondary packaging: 36
Number of units in the packaging: 360
Net unit weight [g]: 52
Grammage [g]: 57.78
Length of a unit pack [cm]: 4.5
Width of a unit pack [cm]: 4.5
Height of a unit pack [cm]: 4
Weight of a cardboard box [kg]: 20.8008

25338 BIURO 04-2010-102 bi

PIR motion sensor

Width of a cardboard box [cm]: 28
Height of a cardboard box [cm]: 35
Length of a cardboard box [cm] : 50
Volume of a cardboard box [m³]: 0.049