


## **25990** NAVI CTX-DS10-B

Ceiling-mounted spotlight fitting

5905339259905















Kanlux NAVI is a family of simple in their form, diverse spotbeam holders with very broad possibilities of use.

#### **GENERAL DATA:**

Colour: black matt

**Necessity of using self-shielding lamps**: yes **Place of assembly**: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m The product is not suitable to be installed on a normally

flammable surface: >35W

The product is not suitable to be covered with a heat-

insulating material: yes

Height [mm]: 26 Diameter [mm]: 75

Assembly hole [mm]: Ø60-70

### TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC Maximum power [W]: max 10

Class of protection against electric shock: III

**Light source**: MR16 **Light source included**: no

**Cap**: Gx5,3

Ambient temperature range to which the product can be

exposed: 5÷25

**Enclosure material**: aluminum alloy **Connection type**: Free cable ends

Wire length [m]: 0.12 Wire diameter [mm<sup>2</sup>]: 0.75

Lighting-fixture angle regulation: none

IP class: 20

#### LOGISTIC DATA:

Packaging method: 50

Number of units in the secondary packaging: 1


Number of units in the packaging: 50

Net unit weight [g]: 46 Grammage [g]: 71.8

Length of a unit pack [cm]: 9 Width of a unit pack [cm]: 4.5 Height of a unit pack [cm]: 9

Weight of a cardboard box [kg]: 3.59 Width of a cardboard box [cm]: 24 Height of a cardboard box [cm]: 20









# **25990** NAVI CTX-DS10-B

Ceiling-mounted spotlight fitting

Length of a cardboard box [cm]: 47 Volume of a cardboard box [m³]: 0.02256

Date of issue: 15.11.2022, 06:16

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

