Kanlux 26035 FULLED GU10-3,3W-CW

LED light source


5905339260352













The appearance similar to the traditional glass halogens, obtained owing to the transparent plastic housing, is the distinguishing feature of Kanlux FULLED. The use of special lens also ensures a lighting effect similar to traditional halogen. Another advantage of these lamps is their illumination angle of 120 allowing for a wide-angle illumination of the selected surface.

GENERAL DATA:

Colour: transparent Lamp designed for decorative lighting: no Compatible with a dimmer: no Width [mm]: 50 Height [mm]: 54 Diameter [mm]: 50 Depth [mm]: 50 Mercury content: no


TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Lamp-power factor: 0.5 Rated power [W]: 3.3 Lampshade material: plastic Light source: PAR16 Diode type: LED SMD Total rated luminous flux [Im]: 295 Useful luminous flux of the light source **Quse** [Im]: 270 Useful luminous flux of the light source **Quse** [Im]: in wide cone (120°) **Colour temperature**: cold white Correlated colour temperature [K]: 6500 **Colour consistency in McAdam ellipses**: ≤6 Colour rendering index: 80 Cap: GU10 Rated lamp-service life [h]: 15000 Number of on/off cycles: ≥15000 Rated beam angle [°]: 120 Rated light level [°]: 120 Lamp rated current [mA]: 27 Annual power consumption [kWh/1000h]: 3 Luminous efficiency of the lamp [lm/W]: 89 **Ignition time [s]**: ≤0,5 Lamp-heating time to 60% of the full luminous flux [s]: Negligible





LED light source






Lamp-heating time to 95% [s]: <2 Lamp premature-failure indicator: <5% po 1000h Lamp service life factor after the period of 6000h [%]: \geq 90 Luminous flux retention factor at the end of rated service life [%]: \geq 70 Luminous flux retention factor after the period of 6000h [%]: \geq 80 Peak luminous intensity [cd]: 85 Light source shape: spot

LOGISTIC DATA:

Packaging method: 20 Number of units in the secondary packaging: 20 Number of units in the packaging: 100 Net unit weight [g]: 26 Grammage [g]: 48.8 Length of a unit pack [cm]: 5.5 Width of a unit pack [cm]: 5.5 Height of a unit pack [cm]: 6.5 Weight of a cardboard box [kg]: 4.88 Width of a cardboard box [kg]: 4.88 Width of a cardboard box [cm]: 29 Height of a cardboard box [cm]: 16.5 Length of a cardboard box [cm]: 59 Volume of a cardboard box [m³]: 0.028232





LED light source

KANLUX S.A. (kat 26035) FULLED GU10-3,3W-CW / LDC (Polar) Luminaire: KANLUX S.A. (kat 26035) FULLED GU10-3,3W-CW Lamps: 1 x FULLED GU10-3,3W-CW 105° 105° M 90° 90 75° 75° 60° 60° 160 45° 45° 240 15° 30° 30 15° 0 cd/klm _____C0 - C180 - C90 - C270

