

26301 OULES AC L-C/M


Ceiling-mounted spotlight fitting

5905339263018

















The Kanlux QULES ceiling eyes are one of the most popular holders with increased IP. They are ideal for mounting in a bathroom or in other places with increased humidity.

GENERAL DATA:

Colour: chrome matte

Necessity of using self-shielding lamps: yes Place of assembly: Recessed mount in the ceiling Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m
The product is not suitable to be covered with a heat-

insulating material: yes

Length [mm]: 83 Width [mm]: 83 Height [mm]: 44

Assembly hole [mm]: Ø71-74

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 10

Class of protection against electric shock: ||

Light source: PAR16 Light source included: no

Cap: GU10

Ambient temperature range to which the product can be

exposed: -20÷35

Enclosure material: aluminum alloy
Connection type: Bolt terminal block
Lighting-fixture angle regulation: none

IP class: 44/20

LOGISTIC DATA:

Packaging method: 50

Number of units in the secondary packaging: 1

Number of units in the packaging: 50

Net unit weight [g]: 210 Grammage [g]: 252.2

Length of a unit pack [cm]: 10.5
Width of a unit pack [cm]: 6
Height of a unit pack [cm]: 10.5
Weight of a cardboard box [kg]: 12.61
Width of a cardboard box [cm]: 33
Height of a cardboard box [cm]: 24
Length of a cardboard box [cm]: 56

Date of issue: 15.11.2022, 06:29


We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.






26301 QULES AC L-C/M

Ceiling-mounted spotlight fitting





Volume of a cardboard box [m³]: 0.044352



We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

