

### **26304** OULES AC O-C/M


Ceiling-mounted spotlight fitting

5905339263049

















The Kanlux QULES ceiling eyes are one of the most popular holders with increased IP. They are ideal for mounting in a bathroom or in other places with increased humidity.

#### **GENERAL DATA:**

Colour: chrome matte

Necessity of using self-shielding lamps: yes Place of assembly: Recessed mount in the ceiling Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m
The product is not suitable to be covered with a heat-

insulating material: yes

Height [mm]: 44 Diameter [mm]: 83

Assembly hole [mm]: Ø71-74

#### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 10

Class of protection against electric shock: ||

**Light source**: PAR16 **Light source included**: no

Cap: GU10

Ambient temperature range to which the product can be

exposed: -20÷35

Enclosure material: aluminum alloy
Connection type: Bolt terminal block
Lighting-fixture angle regulation: none

**IP class**: 44/20

#### LOGISTIC DATA:

Packaging method: 50

Number of units in the secondary packaging: 1

Number of units in the packaging: 50


Net unit weight [g]: 178 Grammage [g]: 220

Length of a unit pack [cm]: 10.5 Width of a unit pack [cm]: 5.5 Height of a unit pack [cm]: 10 Weight of a cardboard box [kg]:

Weight of a cardboard box [kg]: 11
Width of a cardboard box [cm]: 31
Height of a cardboard box [cm]: 23
Length of a cardboard box [cm]: 55

Volume of a cardboard box [m³]: 0.039215









# **26304** QULES AC O-C/M

## Ceiling-mounted spotlight fitting

