


26382 TIBERI CCT 23-29W-B

Downlight luminaire without power supply included

5905339263834



Kanlux TIBERI CCT are reliable flush-mounted luminaires ideal for suspended ceilings, perfect for lighting communication routes, offices and commercial spaces. They are characterized by a durability of 50,000 hours and a luminous efficacy of up to 120 lm/W. Thanks to the high color rendering index (CRI > 90), the light faithfully reproduces colors, and the ability to choose the color temperature (3000K, 3500K, 4000K) allows you to match the lighting to the character of the interior. The luminaires also offer power regulation (Power Switch) in the range of: 15–21 W or 23–29 W. Increased tightness (IP44/20) provides protection against dust, dirt and water splashes, making the luminaires suitable for demanding environments. The lack of a power supply in the set allows you to choose the on-off model (500 mA, 700 mA) or DALI (max. 700 mA). Kanlux TIBERI CCT are available in white and black, and a 5-year warranty confirms their quality and reliability. This is a modern solution that combines functionality with aesthetics.

GENERAL DATA:

Colour: black

Place of assembly: Recessed mount in the ceiling, Recessed mount in the wall

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

The product is not suitable to be covered with a heat-insulating material: yes

A proper LED power supply available in the offer [index] is required for proper operation.: 26385, 26386

Height [mm]: 39

Diameter [mm]: 230

Assembly hole [mm]: Ø210

Mercury content in the lamp [mg]: 0

Integrated LED light source: yes

Number of modules (LED light source): 1

TECHNICAL DATA:

Power-supply current [mA]: 700

Maximum power [W]: max 29,4

26382 TIBERI CCT 23-29W-B

Downlight luminaire without power supply included



Class of protection against electric shock : III
Lampshade material: plastic
Enclosure material: aluminum alloy
Diode type: LED SMD
Luminous flux [lm]: 2970(WW) /3260(WN) /3160(NW)
Useful luminous flux of the light source Φ_{use} [lm] : 4000
Useful luminous flux of the light source Φ_{use} [lm] : in sphere (360°)
Colour temperature: Warm white, white
Correlated colour temperature [K] : 3000/3500/4000
Colour consistency in McAdam ellipses : 6
Colour rendering index: 90
Service life [h] : 50000
Number of on/off cycles : ≥ 50000
Lighting angle [°] : 90
Ambient temperature range to which the product can be exposed : 5÷25
Connection type: Cable terminated with a plug
Range of sections of wires used [mm²] : 0,5-2,5
Supply-cord type: direct current
Power-supply type: direct current
IP class: 44/20
Kształt: round

LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 10
Number of units in the secondary packaging : 1
Number of units in the packaging : 10
Net unit weight [g] : 392
Grammage [g] : 573
Gross unit weight [g] : 518
Length of a unit pack [cm] : 24
Width of a unit pack [cm] : 25
Height of a unit pack [cm] : 6
Weight of a cardboard box [kg] : 5.73
Width of a cardboard box [cm] : 26.5
Height of a cardboard box [cm] : 32
Length of a cardboard box [cm] : 50
Volume of a cardboard box [m³] : 0.0424

ADDITIONAL INFORMATION:

Date of issue: 22.04.2025, 13:52

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

26382 TIBERI CCT 23-29W-B

Downlight luminaire without power supply included

TIBERI CCT 15-21W

	ON ON 1 2	ON ON 1 2	ON ON 1 2	ON ON 1 2
mA	350	400	450	500

mA	K	W	lm
350	3000	15	1570
350	3500	14.5	1700
350	4000	15	1670
400	3000	17	1740
400	3500	16.5	1900
400	4000	17	1860
450	3000	19	1940
450	3500	18.5	2130
450	4000	19	2060
500	3000	21	2090
500	3500	19	2310
500	4000	21	2220

TIBERI CCT 23-29W

	ON ON 1 2	ON ON 1 2	ON ON 1 2	ON ON 1 2
mA	550	600	650	700

mA	K	W	lm
550	3000	22	2400
550	3500	21	2590
550	4000	22	2550
600	3000	24	2580
600	3500	23	2820
600	4000	24	2750
650	3000	27	2800
650	3500	25	3060
650	4000	27	2980
700	3000	29	2970
700	3500	27	3260
700	4000	29	3160

- 5 years Warranty under the terms of the warranty statement, available on our website
- No power supply included.
- The correct LED power supply available in the KANLUX range is required for proper operation

