

## **26448** VARSO HI 36W-NW-O

### Ceiling-mounted LED light fitting

5905339264480

















Kanlux VARSO LED is a family of hermetic ceiling light fixtures with an integrated LED light source. It is a great choice both for developments (housing co-operatives, hotels) and individual households where increased resistance to humidity (IP54) is needed. For lighting particularly large spaces, we recommend 36W Kanlux VARSO HI with a luminous flux up to 3600 lm. Keep in mind that we also offer Kanlux VARSO fixtures with motion sensors (SE).

#### **GENERAL DATA:**

Colour: white

Place of assembly: ceiling mounted Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

Height [mm]: 52 Diameter [mm]: 327 Mercury content: no

Integrated LED light source: yes

#### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 36

Class of protection against electric shock: ||

**Lampshade material**: plastic Diode type: LED SMD

Luminous flux of the light fitting [lm]: 3600

Useful luminous flux of the light source **Φ**use [lm]: 4800 Useful luminous flux of the light source Ouse [lm]: in

sphere (360°)

Colour temperature: white

Correlated colour temperature [K]: 4000 **Colour consistency in McAdam ellipses**: ≤6

Colour rendering index: 80 Service life [h]: 20000

Luminous-flux-retention factor at the end of rated

service life: L70B50

Number of on/off cycles: ≥20000


Lighting angle [°]: 120


Luminous efficiency of the lamp [lm/W]: 100

Ambient temperature range to which the product can be

exposed: -20÷35

Enclosure material: plastic










## **26448** VARSO HI 36W-NW-O

# Ceiling-mounted LED light fitting





**Connection type**: Self-clamping block

Range of sections of wires used [mm<sup>2</sup>]: 0,5-2,5

Lamp-heating time [s]:  $\leq 1$ Lamp-ignition time [s]:  $\leq 0.5$ 

IP class: 54

### LOGISTIC DATA:


Packaging method: 10

Number of units in the secondary packaging: 1

Number of units in the packaging: 10


Net unit weight [g]: 1012 **Grammage [g]**: 1270


Length of a unit pack [cm]: 33.5 Width of a unit pack [cm]: 5.5 Height of a unit pack [cm]: 33.5 Weight of a cardboard box [kg]: 12.7 Width of a cardboard box [cm]: 35.5 Height of a cardboard box [cm]: 35.5 Length of a cardboard box [cm]: 57 Volume of a cardboard box [m3]: 0.071834



KANLUX S.A. (kat 26448) VARSO HI 36W-NW-O / LDC (Polar)

Luminaire: KANLUX S.A. (kat 26448) VARSO HI 36W-NW-O Lamps: 1 x VARSO HI 36W-NW





We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

