Kanlux

26449 VARSO HI 36W-NW-L

Ceiling-mounted LED light fitting

5905339264497

LED techno logy

IP 54

INSTYTUT ZDROWIA PUBLICZNEGO · PZH · NARODOWY · PIB · ODDZIAŁ PRODUKT Z ATESTEM

EA SY instal lation

CE EAC PZH UK CA ⊘

Kanlux VARSO LED is a family of hermetic ceiling light fixtures with an integrated LED light source. It is a great choice both for developments (housing co-operatives, hotels) and individual households where increased resistance to humidity (IP54) is needed. For lighting particularly large spaces, we recommend 36W Kanlux VARSO HI with a luminous flux up to 3600 lm. Keep in mind that we also offer Kanlux VARSO fixtures with motion sensors (SE).

GENERAL DATA:

Colour: white
Place of assembly: ceiling mounted
Place of application: Indoors and outdoors
Minimum distance from the illuminated object: 0,5m
Compatible with a dimmer: no
Length [mm]: 327
Width [mm]: 327
Height [mm]: 52
Mercury content: no
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 36
Class of protection against electric shock: II
Lampshade material: plastic
Diode type: LED SMD
Luminous flux of the light fitting [lm]: 3600
Useful luminous flux of the light source Φuse [lm]: 5000
Useful luminous flux of the light source Φuse [lm]: in sphere (360°)
Colour temperature: white
Correlated colour temperature [K]: 4000
Colour consistency in McAdam ellipses: ≤6
Colour rendering index: 80
Service life [h]: 20000
Luminous-flux-retention factor at the end of rated service life: L70B50
Number of on/off cycles: ≥20000
Lighting angle [°]: 120
Luminous efficiency of the lamp [lm/W]: 100
**Ambient temperature range to which the product can be exposed**: -20÷35

Date of issue: 16.11.2022, 07:22
We reserve the right to make technical changes. The data contained in this material are not legally binding.
Photometry: the results obtained from testing were from a specific sample.

EN

Kanlux

26449 VARSO HI 36W-NW-L

Ceiling-mounted LED light fitting

Enclosure material: plastic
Connection type: Self-clamping block
Range of sections of wires used [mm²]: 0,5-2,5
Lamp-heating time [s]: ≤1
Lamp-ignition time [s]: ≤0,5
IP class: 54

LOGISTIC DATA:

Packaging method: 10
Number of units in the secondary packaging: 1
Number of units in the packaging: 10
Net unit weight [g]: 1248
Grammage [g]: 1500
Length of a unit pack [cm]: 33.5
Width of a unit pack [cm]: 5.5
Height of a unit pack [cm]: 33.5
Weight of a cardboard box [kg]: 15
Width of a cardboard box [cm]: 35.5
Height of a cardboard box [cm]: 35.5
Length of a cardboard box [cm] : 57
Volume of a cardboard box [m³]: 0.071834

KANLUX S.A. (kat 26449) VARSO HI 36W-NW-L / **LDC (Polar)**

Luminaire: KANLUX S.A. (kat 26449) VARSO HI 36W-NW-L
Lamps: 1 x VARSO HI 36W-NW

cd/klm
C0 - C180   C90 - C270

EN