

26463 TAXI SMD P C/M-NW


Recessed light fitting

5905339264633

















Kanlux TAXI SMD is a LED accent luminaire. It can be installed both indoors and outdoors (IP54). A perfect choice for decorative lighting of stairs and platforms.

GENERAL DATA:

Colour: chrome matte

Place of assembly: Recessed mount in the wall Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,1m

Compatible with a dimmer: no

Length [mm]: 110 **Width [mm]**: 50 Height [mm]: 44

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 0.6

Class of protection against electric shock: |

Diode type: LED SMD Luminous flux [lm]: 10 Colour temperature: white

Correlated colour temperature [K]: 4000 **Colour consistency in McAdam ellipses**: ≤6

Colour rendering index: 80 Service life [h]: 20000

Number of on/off cycles: ≥ 10000

Luminous efficiency of the lamp [lm/W]: 17

Ambient temperature range to which the product can be


exposed: -20÷35

Enclosure material: Metal

Panel/frame material: stainless steel Protective glass material: glass Connection type: Free cable ends

Wire length [m]: 0.22 Wire diameter [mm²]: 0.75 Lamp-heating time [s]: ≤ 1 Lamp-ignition time [s]: ≤ 0.5

IP class: 54







26463 TAXI SMD P C/M-NW

Recessed light fitting



LOGISTIC DATA:

Packaging method: 10

Number of units in the secondary packaging: 10

Number of units in the packaging: 40

Net unit weight [g]: 204 Grammage [g]: 251.75

Length of a unit pack [cm]: 12.5 Width of a unit pack [cm]: 5.5 Height of a unit pack [cm]: 7

Weight of a cardboard box [kg]: 10.07 Width of a cardboard box [cm]: 29 Height of a cardboard box [cm]: 34 Length of a cardboard box [cm]: 31

Volume of a cardboard box [m³]: 0.030566

