


PIR motion sensor

5905339268204



Kanlux SENTO is an electronic sensor for movement detection. Its exceptionality lies in the fact that as many as three infrared detectors are installed in one sensor. This guarantees an unprecedented sensitivity and allows you to capture even the slightest movement. Kanlux SENTO, due to its unusual features, is referred to as a presence detector.

### GENERAL DATA:

**Colour:** white  
**Place of assembly:** wall mounted, ceiling mounted  
**Place of application:** Indoors  
**Micro-interval between relay contacts:** yes  
**Length [mm]:** 102  
**Width [mm]:** 102  
**Height [mm]:** 60  
**Sensitivity regulation:** yes

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC  
**Rated frequency [Hz]:** 50  
**Class of protection against electric shock:** II  
**Material:** plastic  
**Ambient temperature range to which the product can be exposed:** 5÷25  
**Sensor type:** 3xPIR  
**Connection type:** Terminal block  
**Range of sections of wires used [mm<sup>2</sup>]:** 0,75÷1,5  
**Sensor-operation time [second-minute]:** 10-30  
**sensor working angle [°]:** H360/V120  
**Maximum operating time [min]:** 30  
**Minimum operating time[s]:** 10  
**Maximum power [VA]:** 2000  
**Illumination-level setpoint by which the sensor detects movement [lx]:** 3-2000  
**IP class:** 20  
**Sensor range[m]:** max 10

### LOGISTIC DATA:

**Packaging method:** 50  
**Number of units in the secondary packaging:** 1  
**Number of units in the packaging:** 50  
**Net unit weight [g]:** 142  
**Grammage [g]:** 199.4  
**Length of a unit pack [cm]:** 11  
**Width of a unit pack [cm]:** 7

### PIR motion sensor



**Height of a unit pack [cm]:** 11  
**Weight of a cardboard box [kg]:** 9.97  
**Width of a cardboard box [cm]:** 39  
**Height of a cardboard box [cm]:** 24  
**Length of a cardboard box [cm]:** 56  
**Volume of a cardboard box [m<sup>3</sup>]:** 0.052416

