

Ceiling-mounted LED light fitting

5905339269850



Kanlux VARSO LED is a family of hermetic ceiling light fixtures with an integrated LED light source. It is a great choice both for developments (housing co-operatives, hotels) and individual households where increased resistance to humidity (IP54) is needed. For lighting particularly large spaces, we recommend 36W Kanlux VARSO HI with a luminous flux up to 3600 lm. Keep in mind that we also offer Kanlux VARSO fixtures with motion sensors (SE).


GENERAL DATA:

Colour: white
Place of assembly: ceiling mounted
Place of application: Indoors and outdoors
Micro-interval between relay contacts: yes
Minimum distance from the illuminated object: 0,5m
Compatible with a dimmer: no
Wykrywanie ruchu: yes
Height [mm]: 52
Diameter [mm]: 327
Sensitivity regulation: yes
Mercury content: no
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 36
Class of protection against electric shock: II
Lampshade material: plastic
Diode type: LED SMD
Luminous flux of the light fitting [lm]: 3600
Useful luminous flux of the light source Φ_{use} [lm]: 4800
Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)
Colour temperature: white
Correlated colour temperature [K]: 4000
Colour consistency in McAdam ellipses: ≤ 6
Colour rendering index: 80
Service life [h]: 20000
Luminous-flux-retention factor at the end of rated service life: L70B50
Number of on/off cycles: ≥ 20000
Lighting angle [°]: 120
Luminous efficiency of the lamp [lm/W]: 100

Ceiling-mounted LED light fitting



Ambient temperature range to which the product can be exposed: -20÷35

Enclosure material: plastic

Sensor type: microwave

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 0,5-2,5

Sensor-operation time [second-minute]: 5-5

Lamp-heating time [s]: ≤1

Lamp-ignition time [s]: ≤0,5

Sensor-operation frequency [MHz]: 5,8

sensor working angle [°]: 360

Illumination-level setpoint by which the sensor detects movement [lx]: 2/10/50/off

IP class: 54

Sensor range[m]: max 9

LOGISTIC DATA:

Packaging method: 10

Number of units in the secondary packaging: 1

Number of units in the packaging: 10

Net unit weight [g]: 992

Grammage [g]: 1250

Length of a unit pack [cm]: 33.5

Width of a unit pack [cm]: 5.5

Height of a unit pack [cm]: 33.5


Weight of a cardboard box [kg]: 12.5

Width of a cardboard box [cm]: 35.5

Height of a cardboard box [cm]: 35.5

Length of a cardboard box [cm]: 57

Volume of a cardboard box [m³]: 0.071834



26985 VARSO HI 36W-NW-O-SE

Ceiling-mounted LED light fitting

KANLUX S.A. (kat 26985) VARSO HI 36W-NW-O-SE / LDC (Polar)

Luminaire: KANLUX S.A. (kat 26985) VARSO HI 36W-NW-O-SE
Lamps: 1 x VARSO HI 36W-NW

