27253 KMB6-C63/1

Overcurrent circuit breaker, 1P

5905339272539



Circuit breaker with overcurrent protection is used to protect cables against overloads and short circuits in installations and devices.

GENERAL DATA:

Place of assembly: na szynę TH35
Norm: PN-EN 60898-1
Length [mm]: 76
Width [mm]: 17.5
Height [mm]: 82

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC
Rated current [A]: 63
Rated frequency [Hz]: 50
Ambient temperature range to which the product can be exposed: 5÷40
Range of sections of wires used [mm²]: 1÷25
Release characteristics: C
Energy-limit class: 3
Number of modules: 1
Rated short-circuit current [A]: 6000
IP class: 20
Rated insulation voltage UI [V]: 500
Number of poles: 1

LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 12
Number of units in the secondary packaging: 12
Number of units in the packaging: 120
Net unit weight [g]: 106
Grammage [g]: 115
Length of a unit pack [cm]: 2
Width of a unit pack [cm]: 7.5
Height of a unit pack [cm]: 8.5
Weight of a cardboard box [kg]: 13.8
Width of a cardboard box [cm]: 24.5
Height of a cardboard box [cm]: 20
Length of a cardboard box [cm] : 46
Volume of a cardboard box [m³]: 0.02254

We reserve the right to make technical changes. The data contained in this material are not legally binding.
Photometry: the results obtained from testing were from a specific sample.

EN