


T8 LED tube linear fittings

5905339274113







Colour: black Place of assembly: for suspension on the ceiling Place of application: Indoors Minimum distance from the illuminated object: 0,5m Fixture lighting direction: down Power supply of T8 LED fluorescent lamps: Unilateral Length [mm]: 630 Width [mm]: 60 Height [mm]: 69

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 18 Class of protection against electric shock: I Lampshade material: plastic Light source: T8 LED Light source included: no Cap: G13 Ambient temperature range to which the product can be exposed: 5÷25 Shade type: matt Enclosure material: aluminum alloy Connection type: Self-clamping block Range of sections of wires used [mm²]: 1,5÷2,5 IP class: 20

LOGISTIC DATA:


Packaging method: 1 Number of units in the secondary packaging: 1 Number of units in the packaging: 1 Net unit weight [g]: 1100 Grammage [g]: 1280 Length of a unit pack [cm]: 74 Width of a unit pack [cm]: 74 Width of a unit pack [cm]: 11 Height of a cardboard box [kg]: 1.28 Width of a cardboard box [kg]: 1.28 Width of a cardboard box [cm]: 11 Height of a cardboard box [cm]: 7 Length of a cardboard box [cm]: 74 Volume of a cardboard box [m³]: 0.005698



T8 LED tube linear fittings




KANLUX S.A. (kat 27411) ALIN 4LED 1X60-B + GLASSv4 / LDC (Polar) Luminaire: KANLUX S.A. (kat 27411) ALIN 4LED 1X60-B + GLASSv4 Lamps: 1 x T8 LED GLASSv4 9W-NW



- C90 - C270

KANLUX S.A. (kat 27411) ALIN 4LED 1X60-B + GLASSv3 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 27411) ALIN 4LED 1X60-B + GLASSv3 Lamps: 1 x T8 LED GLASSv3 9W-NW




cd/klm C0 - C180 - C90 - C270



T8 LED tube linear fittings

KANLUX S.A. (kat 27411) ALIN 4LED 1X60-B + GLASSv2 / LDC (Polar) Luminaire: KANLUX S.A. (kat 27411) ALIN 4LED 1X60-B + GLASSv2 Lamps: 1 x T8 LED GLASSv2 9W-WW



- C90 - C270

KANLUX S.A. (kat 27411) ALIN 4LED 1X60-B + Miledo / LDC (Polar)



