


T8 LED tube linear fittings

5905339274205









Colour: black Place of assembly: ceiling mounted Place of application: Indoors Minimum distance from the illuminated object: 0,5m Fixture lighting direction: down Power supply of T8 LED fluorescent lamps: Unilateral Length [mm]: 1240 Width [mm]: 60 Height [mm]: 69

## TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 36 Class of protection against electric shock: I Lampshade material: plastic Light source: T8 LED Light source included: no Cap: G13 Ambient temperature range to which the product can be exposed: 5÷25 Shade type: matt Enclosure material: aluminum alloy Connection type: Self-clamping block Range of sections of wires used [mm<sup>2</sup>]: 1,5÷2,5 IP class: 20

## LOGISTIC DATA:

Packaging method: 1 Number of units in the secondary packaging: 1 Number of units in the packaging: 1 Net unit weight [g]: 1700 Grammage [g]: 2030 Length of a unit pack [cm]: 136 Width of a unit pack [cm]: 11 Height of a unit pack [cm]: 7 Weight of a cardboard box [kg]: 2.03 Width of a cardboard box [kg]: 2.03 Width of a cardboard box [cm]: 11 Height of a cardboard box [cm]: 11 Height of a cardboard box [cm]: 126 Volume of a cardboard box [m<sup>3</sup>]: 0.010472



## T8 LED tube linear fittings

KANLUX S.A. (kat 27420) ALIN 4LED 1X120-B-NT + GLASSv4 / LDC (Polar) Luminaire: KANLUX S.A. (kat 27420) ALIN 4LED 1X120-B-NT + GLASSv4 Lamps: 1 x T8 LED GLASSv4 18W-NW

