



27421 ALIN 4LED 1X120-SR-NT

T8 LED tube linear fittings

5905339274212



GENERAL DATA:

Colour: silver

Place of assembly: ceiling mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Fixture lighting direction: down

Power supply of T8 LED fluorescent lamps: Unilateral

Length [mm]: 1240

Width [mm]: 60

Height [mm]: 69

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: max 36

Class of protection against electric shock: I

Lampshade material: plastic

Light source: T8 LED

Light source included: no

Cap: G13

Ambient temperature range to which the product can be exposed: 5÷25

Shade type: matt

Enclosure material: aluminum alloy

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 1,5÷2,5

IP class: 20

LOGISTIC DATA:

Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 1700

Grammage [g]: 2030

Length of a unit pack [cm]: 136

Width of a unit pack [cm]: 11

Height of a unit pack [cm]: 7

Weight of a cardboard box [kg]: 2.03

Width of a cardboard box [cm]: 11

Height of a cardboard box [cm]: 7

Length of a cardboard box [cm]: 136


Volume of a cardboard box [m³]: 0.010472

27421 ALIN 4LED 1X120-SR-NT

T8 LED tube linear fittings


KANLUX S.A. (kat 27421) ALIN 4LED 1X120-SR-NT + GLASSv4 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 27421) ALIN 4LED 1X120-SR-NT + GLASSv4
Lamps: 1 x T8 LED GLASSv4 18W-NW



KANLUX S.A. (kat 27421) ALIN 4LED 1X120-SR-NT + GLASSv3 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 27421) ALIN 4LED 1X120-SR-NT + GLASSv3
Lamps: 1 x T8 LED GLASSv3 18W-NW



27421 ALIN 4LED 1X120-SR-NT

T8 LED tube linear fittings

KANLUX S.A. (kat 27421) ALIN 4LED 1X120-SR-NT + Miledo / LDC (Polar)

Luminaire: KANLUX S.A. (kat 27421) ALIN 4LED 1X120-SR-NT + Miledo
Lamps: 1 x T8 LED 18W/NW

