

27571 RITI GU10 B/G

Ceiling-mounted spotlight fitting 5905339275714



















The Kanlux RITI is in aluminium, the sandblasted surface structure is matte-lacquered, and the reflector is covered with a layer of gold-copper lacquer with a shiny pigment. The Kanlux RITI series is characterised by good-quality workmanship and modern design. It can be successfully used as a stand-alone lighting system, or as a combination of several fixtures.

GENERAL DATA:

Colour: black/gold

Place of assembly: ceiling mounted Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Height [mm]: 110 Diameter [mm]: 85

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 10

Class of protection against electric shock: I

Light source: PAR16 **Light source included**: no

Cap: GU10

Ambient temperature range to which the product can be

exposed: 5÷25

Enclosure material: aluminum alloy **Connection type**: Bolt terminal block

Range of sections of wires used [mm²]: 1÷2,5

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 20

Number of units in the secondary packaging: 1

Number of units in the packaging: 20 Number of units per layer on a pallet: 160

Net unit weight [g]: 300 Grammage [g]: 363

Gross unit weight [g]: 330 Length of a unit pack [cm]: 9 Width of a unit pack [cm]: 9

Date of issue: 07.02.2024, 12:31


We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





27571 RITI GU10 B/G

Ceiling-mounted spotlight fitting






Height of a unit pack [cm]: 12

Weight of a cardboard box [kg]: 7.26 Width of a cardboard box [cm]: 20.5 Height of a cardboard box [cm]: 26 Length of a cardboard box [cm]: 47 Volume of a cardboard box [m³]: 0.025051

KANLUX S.A. (kat 27571) RITI GU10 B/G + TOMI LED5W / LDC (Polar)



C90 - C270

